

Application No. 10/733,325
Reply to Office Action mailed May 12, 2005

Patent
Attorney Docket No. 86200-11

I. AMENDMENTS TO THE CLAIMS

Please find below a listing of claims that will replace all prior versions, and listings, of claims in the application:

Listing of claims:

1. (original) An apparatus for treating a substrate sensitive to electromagnetic radiation, comprising;
 - a) a first mask for conditioning a first beam of electromagnetic radiation and producing a first conditioned beam of electromagnetic radiation;
 - b) a second mask for conditioning a second beam of electromagnetic radiation and producing a second conditioned beam of electromagnetic radiation;
 - c) the first and the second conditioned beams of electromagnetic radiation being characterized in that:
 - i) when they are directed toward the substrate sensitive to electromagnetic radiation, a treatment area of the substrate sensitive to electromagnetic radiation is exposed to electromagnetic radiation;
 - ii) the first and the second conditioned beams of electromagnetic radiation interact to create an interference pattern over a limited portion of the treatment area.
2. (currently amended) An apparatus as defined in claim [[1]] 53, wherein the first and the second conditioned beams of electromagnetic radiation induce an index of refraction change in the substrate sensitive to electromagnetic radiation, ~~wherein the treatment area has two portions, a first portion and a second portion, the second portion corresponding to the limited portion,~~ the index of refraction of the substrate sensitive to electromagnetic radiation being modified differently over the first portion than over the second portion.

Application No. 10/733,325
Reply to Office Action mailed May 12, 2005

Patent
Attorney Docket No. 86200-11

3. (original) An apparatus as defined in claim 2, wherein the index of refraction is altered substantially uniformly over the first portion.
4. (currently amended) An apparatus as defined in claim ~~[[4]]~~ 3, wherein the index of refraction is altered in a non-uniform manner over the second portion.
5. (original) An apparatus as defined in claim 4, wherein the substrate sensitive to electromagnetic radiation is a waveguide.
6. (original) An apparatus as defined in claim 5, wherein the index of refraction changes periodically over the second portion.
7. (original) An apparatus as defined in claim 6, wherein the second portion forms a Bragg grating.
8. (original) An apparatus as defined in claim 7, wherein the Bragg grating has an apodization.
9. (original) An apparatus as defined in claim 8, wherein the apodization is a Gaussian apodization.
10. (original) An apparatus as defined in claim 9, wherein the index of refraction is altered substantially uniformly over the first portion to form a base value, the Gaussian apodization being symmetrical on either side of the base value.
11. (original) An apparatus as defined in claim 10, wherein the waveguide defines an electromagnetic radiation propagation axis, the Gaussian apodization forming an amplitude profile of the Bragg grating along the electromagnetic radiation propagation axis.

Application No. 10/733,325
Reply to Office Action mailed May 12, 2005

Patent
Attorney Docket No. 86200-11

12. (original) An apparatus as defined in claim 5, wherein the waveguide is an optical fiber.
13. (original) An apparatus as defined in claim 12, wherein the first beam of electromagnetic radiation and the second beam of electromagnetic radiation belong to different diffractive orders to create the interference pattern.
14. (currently amended) An apparatus as defined in claim 13, comprising a source of electromagnetic radiation from which ~~is derived~~ are derivable the first and the second beams of electromagnetic radiation.
15. (original) An apparatus as defined in claim 14, comprising a diffractive mask subjected to exposition of electromagnetic radiation by the source of electromagnetic radiation to produce the first and the second beams of electromagnetic radiation.
16. (currently amended) An apparatus as defined in claim 15, including an optical system to focus the first and the second conditioned beams of electromagnetic radiation toward the optical fiber.
17. (original) An apparatus as defined in claim 16, wherein said source of electromagnetic radiation is coherent.
18. (original) An apparatus as defined in claim 17, wherein the coherent electromagnetic radiation is a UV laser.
19. (original) A substrate sensitive to electromagnetic radiation having an index of refraction modified by the apparatus defined in claim 1.
20. (currently amended) A method for inducing a modification of the index of refraction of a substrate sensitive to electromagnetic radiation, comprising;

Application No. 10/733,325
Reply to Office Action mailed May 12, 2005

Patent
Attorney Docket No. 86200-11

- a) conditioning with a first mask a first beam of electromagnetic radiation and producing a first conditioned beam of electromagnetic radiation;
 - b) conditioning with a second mask a second beam of electromagnetic radiation and producing a second conditioned beam of electromagnetic radiation;
 - c) directing the first and the second conditioned beams of electromagnetic radiation toward the substrate sensitive to electromagnetic radiation to expose a treatment area of the substrate to ~~[[to]]~~ electromagnetic radiation;
 - d) the first and the second conditioned beams of electromagnetic radiation interact to create an interference pattern over a limited portion of the treatment area.
21. (currently amended) A method as defined in claim ~~[[20]]~~ 55, wherein ~~the treatment area has two portions, a first portion and a second portion, the second portion corresponding to the limited portion,~~ the index of refraction of the substrate sensitive to electromagnetic radiation ~~[[being]]~~ is modified differently over the first portion than over the second portion.
22. (original) A method as defined in claim 21, wherein the index of refraction is altered substantially uniformly over the first portion.
23. (original) A method as defined in claim 22, wherein the index of refraction is altered in a non-uniform manner over the second portion.
24. (currently amended) A method as defined in claim ~~[[22]]~~ 23, wherein the substrate sensitive to electromagnetic radiation is a waveguide.
25. (original) A method as defined in claim 24, wherein the index of refraction changes periodically over the second portion.
26. (original) A method as defined in claim 25, wherein the second portion forms a Bragg grating.

Application No. 10/733,325
Reply to Office Action mailed May 12, 2005

Patent
Attorney Docket No. 86200-11

27. (original) A method as defined in claim 26, wherein the Bragg grating has an apodization.
28. (original) A method as defined in claim 27, wherein the apodization is a Gaussian apodization.
29. (original) A method as defined in claim 28, wherein the index of refraction is altered substantially uniformly over the first portion to form a base value, the Gaussian apodization being symmetrical on either side of the base value.
30. (original) A method as defined in claim 29, wherein the waveguide defines an electromagnetic radiation propagation axis, the Gaussian apodization forming an amplitude profile of the Bragg grating along the electromagnetic radiation propagation axis.
31. (original) A method as defined in claim 24, wherein the waveguide is an optical fiber.
32. (original) A method as defined in claim 31, wherein the first beam of electromagnetic radiation and the second beam of electromagnetic radiation belong to different diffractive orders to create the interference pattern.
33. (currently amended) A method as defined in claim 32, comprising providing a source of electromagnetic radiation from which is derived the first and the second beams of electromagnetic radiation.
34. (currently amended) A method as defined in claim 33, comprising providing a diffractive mask exposed to electromagnetic radiation by the source of electromagnetic radiation to produce the first and the second beams of electromagnetic radiation.

Application No. 10/733,325
Reply to Office Action mailed May 12, 2005

Patent
Attorney Docket No. 86200-11

35. (currently amended) A method as defined in claim 34, including providing an optical system to focus the first and the second conditioned beams of electromagnetic radiation toward the optical fiber.
36. (original) A method as defined in claim 35, wherein said source of electromagnetic radiation is coherent.
37. (original) A method as defined in claim 36, wherein the coherent electromagnetic radiation is a UV laser.
38. (original) A substrate sensitive to electromagnetic radiation processed by the method defined in claim 20.
39. (withdrawn) An apparatus for inducing a modification of the index of refraction of a substrate sensitive to electromagnetic radiation, said apparatus comprising:
- a) an optical system for generating a first beam of electromagnetic radiation and a second beam of electromagnetic radiation different from the first beam of electromagnetic radiation;
 - b) said optical system establishing a first propagation path for the first beam of electromagnetic radiation and a second propagation path for said second beam of electromagnetic radiation, said first and second paths causing the first and the second beams of electromagnetic radiation to converge toward the substrate sensitive to electromagnetic radiation and expose a treatment area on the substrate to electromagnetic radiation, the first and the second beams of electromagnetic radiation interacting to create an interference pattern over a limited portion of the treatment area.
40. (withdrawn) An apparatus as defined in claim 39, wherein the treatment area has two portions, a first portion and a second portion, the second portion corresponding to the limited portion, the index of refraction of the substrate sensitive to electromagnetic

Application No. 10/733,325
Reply to Office Action mailed May 12, 2005

Patent
Attorney Docket No. 86200-11

radiation being modified differently over the first portion than over the second portion.

41. (withdrawn) An apparatus as defined in claim 40, wherein the index of refraction is altered substantially uniformly over the first portion.
42. (withdrawn) An apparatus as defined in claim 41, wherein the index of refraction is altered in a non-uniform manner over the second portion.
43. (withdrawn) An apparatus as defined in claim 42, wherein the substrate sensitive to electromagnetic radiation is a waveguide.
44. (withdrawn) An apparatus as defined in claim 43, wherein the index of refraction changes periodically over the second portion.
45. (withdrawn) An apparatus as defined in claim 44, wherein the second portion forms a Bragg grating.
46. (withdrawn) An apparatus as defined in claim 45, wherein the Bragg grating has an apodization.
47. (withdrawn) An apparatus as defined in claim 46, wherein the apodization is a double Gaussian apodization.
48. (original) A method for inducing a modification of the index of refraction of a substrate sensitive to electromagnetic radiation, said method comprising:
 - a) generating a first beam of electromagnetic radiation and a second beam of electromagnetic radiation different from the first beam of electromagnetic radiation;
 - b) directing the first and the second beams of electromagnetic radiation toward the substrate sensitive to electromagnetic radiation to expose a treatment area

Application No. 10/733,325
Reply to Office Action mailed May 12, 2005

Patent
Attorney Docket No. 86200-11

on the substrate to electromagnetic radiation, the first and the second beams of electromagnetic radiation interacting to create an interference pattern over a limited portion of the treatment area.

49. (original) An apparatus as defined in claim 1, wherein the first and the second conditioned beams of electromagnetic radiation induce a predetermined gaseous profile in the substrate.
50. (original) An apparatus as defined in claim 49, wherein the gaseous profile is a hydrogen profile.
51. (original) An apparatus as defined in claim 1, wherein said first mask imparts a first cross-sectional shape to the first beam of electromagnetic radiation, said second mask imparts a second cross-sectional shape to the second beam of electromagnetic radiation, the first cross-sectional shape being different from the second cross-sectional shape.
52. (original) An apparatus as defined in claim 51, wherein said first mask imparts a phase shift to the first beam of electromagnetic radiation.
53. (new) An apparatus as defined in claim 1, wherein the treatment area has:
 - a first portion exposed to only one of the first and the second conditioned beams of electromagnetic radiation; and
 - a second portion exposed to both the first and the second conditioned beams of electromagnetic radiation, the second portion being the limited portion.
54. (new) An apparatus as defined in claim 53, wherein the second portion is surrounded by the first portion.
55. (new) A method as defined in claim 20, wherein the treatment area has:

Application No. 10/733,325
Reply to Office Action mailed May 12, 2005

Patent
Attorney Docket No. 86200-11

- a first portion exposed to only one of the first and the second conditioned beams of electromagnetic radiation; and
 - a second portion exposed to both the first and the second conditioned beams of electromagnetic radiation, the second portion being the limited portion.
56. (new) A method as defined in claim 55, wherein the second portion is surrounded by the first portion.
57. (new) An apparatus for creating a grating on an optical waveguide, said apparatus comprising an optical system adapted to:
- generate a first beam of electromagnetic radiation having a first cross-sectional area;
 - generate a second beam of electromagnetic radiation having a second cross-sectional area different from the first cross-sectional area; and
 - direct the first beam of electromagnetic radiation and the second beam of electromagnetic radiation toward a portion of the optical waveguide such that the first beam of electromagnetic radiation and the second beam of electromagnetic radiation interact and create a grating at the portion of the optical waveguide.
58. (new) An apparatus as defined in claim 57, wherein the grating is a Bragg grating.
59. (new) A method for use in creating a grating on an optical waveguide, said method comprising:
- generating first and second beams of electromagnetic radiation having different cross-sectional shapes;
 - directing the first and second beams of electromagnetic radiation toward a treatment area on the optical waveguide to induce in the optical waveguide an index of refraction change.

Application No. 10/733,325
Reply to Office Action mailed May 12, 2005

Patent
Attorney Docket No. 86200-11

60. (new) A method as defined in claim 59, wherein the first and second beams of electromagnetic radiation partially overlap in the treatment area.
61. (new) A method as defined in claim 60, wherein the first and second beams of electromagnetic radiation induce a non-linear index of refraction change.
62. (new) An apparatus for use in creating a grating on an optical waveguide, said apparatus comprising an optical system for:
- generating first and second beams of electromagnetic radiation;
 - directing the first and second beams of electromagnetic radiation toward the optical waveguide;
 - the first and second beams of electromagnetic radiation affecting respective portions of the optical waveguide that overlap one another and induce an index of refraction change in the optical waveguide.
63. (new) An apparatus as defined in claim 62, wherein the index of refraction change varies non-linearly on the optical waveguide.
64. (new) An apparatus as defined in claim 63, wherein the index of refraction change forms a Bragg grating.
65. (new) An apparatus for use in creating a grating on an optical waveguide, said apparatus comprising an optical system for:
- generating first and second beams of electromagnetic radiation;
 - conditioning and directing the first and second beams of electromagnetic radiation toward a treatment area of the optical waveguide to cause the first and second beams of electromagnetic radiation to interact and induce a non-linear index of refraction change over the treatment area.
66. (new) An apparatus as defined in claim 65, wherein the non-linear index of refraction change creates a Bragg grating.

Application No. 10/733,325
Reply to Office Action mailed May 12, 2005

Patent
Attorney Docket No. 86200-11

67. (new) A method for use in creating a grating on an optical waveguide, said method comprising:
- generating first and second beams of electromagnetic radiation;
 - conditioning and directing the first and second beams of electromagnetic radiation toward a treatment area of the optical waveguide to cause the first and second beams of electromagnetic radiation to interact and induce a non-linear index of refraction change over the treatment area.